BenchPro™ BP-SR

Shipping Bench Scale with Roller Conveyor



Standard Features

- · Simple operation, easy to set up
- · Large six-digit backlight LCD display with 1 in (29 mm) characters protected by heavy duty tempered glass
- Powered USB HID point of sale interface kg model only
- Nine-pin RS-232 interface for use with SMA and NCI protocols
- Four AA alkaline battery operation for portability
- · Gravitational compensation allows for adjustment of factory calibration to meet your local gravity setting, non-approved

APPROVALS



Measurement Canada Approved



Specifications

Dynamic Response:

Response time for stable weight: 0 - 1,000d, 1,000 ms, maximum mean average 1,000d +, 1,500 ms, maximum mean average

Internal Resolution:

500,000 internal count minimum

Overload Protection:

Corner & center overload protection

In-line Power Supply (included)
Input: 100-240 VAC, +10% -15%, 3-wire w/ground
Standard terminated with USA 3-prong plug Output: 12V at .1 Amps DC minimum Frequency: 50/60 Hz +/-3 Hz, standard

Approvals: UL, CE, EN, CUL

USB HID:

USB 2.0 full speed; Vendor ID: 1C19; Product ID: 0002

Construction:

Powder coat painted mild steel base plate and load bridge with stainless steel roller conveyor

Display:

Minimum key press life of 500,000 cycles, ABS plastic housing 6 annunciators to indicate Zero, Gross/Brutto, Net, W1/W2/W3 multi-range 4 buttons: Units, Tare, On/Off, F1

RS-232 Cable (included):

10 ft DB 9-pin male to female, straight pass through and null modem

USB Cable (included):

46 in (1168.4 mm) A/B type USB cable

Approvals:

NTEP COC # 17-002 Canada Weights and Measures: AM - 6050 CE Marked

Warranty:

Two-year limited warranty





Part Number/Price

| Part # | Platform Capacity | Dimensions | Est. Weight | Price |
|--------|------------------------------|------------|-------------|---------|
| 182996 | 150 x 0.05 lb (75 x 0.02 kg) | 12 x 16 in | 41 lb | Consult |
| 182394 | 100 x 0.02 lb (50 x 0.01 kg) | 18 x 18 in | 77 lb | Consult |
| 182381 | 150 x 0.05 lb (75 x 0.02 kg) | 18 x 18 in | 77 lb | Consult |
| 182386 | 300 x 0.1 lb (150 x 0.05 kg) | 18 x 18 in | 77 lb | Consult |
| 182398 | 300 x 0.1 lb (150 x 0.05 kg) | 20 x 20 in | 94 lb | Consult |
| 182402 | 300 x 0.1 lb (150 x 0.05 kg) | 24 x 24 in | 131 lb | Consult |

Options/Accessories

| Part # | Description | Est. Weight | Price |
|--------|--|-------------|---------|
| 180901 | Second Customer display, BenchPro BP-SR no keyboard with 68 in cable | 4 lb | Consult |
| 174784 | Second Remote operator display, BenchPro BP-SR with 68 in cable | 4 lb | Consult |
| 183103 | 16 in (H) tabletop display post for use with second display, customer or remote operator | 4 lb | Consult |
| 178501 | USB-RS-232 serial adapter | 1 lb | Consult |

Dimensions - Inches

| | A | В | C | D |
|---------|----|----|-------|------|
| 12 x 16 | 12 | 16 | 15.30 | 5.95 |
| 18 x 18 | 18 | 18 | 21.10 | 6.50 |
| 20 x 20 | 20 | 20 | 23.10 | 6.50 |
| 24 x 24 | 24 | 24 | 27.10 | 6.50 |







