

BenchPro™ BP-SB

Shipping Bench Scale with Ball Top Shroud



Standard Features

- Simple operation, easy to set up
- Large six-digit backlight LCD display with 1 in (29 mm) characters protected by heavy duty tempered glass
- Powered USB HID point of sale interface – kg model only
- Nine-pin RS-232 interface for use with SMA and NCI protocols
- Four AA alkaline battery operation for portability
- Gravitational compensation allows for adjustment of factory calibration to meet your local gravity setting, non-approved

APPROVALS



Measurement
Canada
Approved



Specifications

Dynamic Response:

Response time for stable weight:
0 - 1,000d, 1,000 ms, maximum mean average
1,000d +, 1,500 ms, maximum mean average

Internal Resolution:

500,000 internal count minimum

Overload Protection:

Corner & center overload protection

Power:

In-line Power Supply (included)

Input: 100-240 VAC, +10% -15%, 3-wire w/ground

Standard terminated with USA 3-prong plug

Output: 12V at .1 Amps DC minimum

Frequency: 50/60 Hz +/-3 Hz, standard

Approvals: UL, CE, EN, CUL

USB HID:

USB 2.0 full speed; Vendor ID: 1C19;

Product ID: 0002

Construction:

Powder coat painted mild steel base plate and load bridge. Carbon steel ball with carbon steel zinc plated housing. Stainless steel shroud.

Display:

Minimum key press life of 500,000 cycles,

ABS plastic housing

6 annunciators to indicate Zero, Gross/Brutto, Net,

W1/W2/W3 multi-range

4 buttons: Units, Tare, On/Off, F1

RS-232 Cable (included):

10 ft DB 9-pin male to female, straight pass through and null modem

USB Cable (included):

46 in (1168.4 mm) A/B type USB cable

Approvals:


NTEP COC # 17-002

Canada Weights and Measures: AM - 6050

CE Marked

Warranty:

Two-year limited warranty



WALZ

Label & Mailing Systems

624 High Point Ln, East Peoria, IL 61611-9329

(309) 698-1500 T/F (877) 971-1500

www.walzeq.com email: walz@walzeq.com