FALCON™ X4





CHOICE OF WINDOWS EMBEDDED OR ANDROID™ OPERATING SYSTEMS

Legendary Falcon with upgraded performance! The Falcon™ X4 mobile computer features a high performance multicore 1 GHz architecture that offers blazing speed when running Windows Embedded Compact OS and allows easy upgradeability to the Android™ OS. Users will never run out of memory with the standard 1 GB RAM and 8 GB Flash.

REAL-TIME DATA CAPTURE AND COMMUNICATIONS

Capture bar codes using Datalogic 1D and 2D imaging technologies. Communicate over a superior TI 802.11 a/b/g/n radio with CCX v4 compliance and MIMO technology for improved connectivity and coverage, or through wired standards including USB Hi-Speed, RS-232, Modem and Ethernet. Bluetooth® wireless technology v4 provides support for the new low energy mode (BLE) and for improved voice recognition via wide band audio.

ERGONOMIC AND RUGGED

Users feel the full shift difference of ergonomic handheld and pistol grip form factors to balance a 3.5 inch crystal clear display, full numeric or alphanumeric back-lit keyboards, and a one piece 5,200 mAh battery. With the best ergonomics in this market segment, the Falcon X4 mobile computer reduces operator fatigue with no compromise in terms of reliability and robustness, resisting harsh environments, repeated drops, strong shocks and repetitive tumbles.

EASY AND INTUITIVE

Develop custom solutions using the industry-leading Datalogic Software Development Kit (SDK). Deploy quickly with the included Datalogic utilities or your preferred device management solution. Manage your installed devices using the pre-licensed Wavelink Avalanche or leverage the pre-licensed Wavelink Terminal Emulation (WEC7 only).

FEATURES

- Full-shift hot swappable battery
- 3.5 inch touchscreen display
- Ruggedized with 1.8 m / 6.0 ft drop to concrete and IP65 sealing rating
- Choice of 1D or 2D imagers featuring Datalogic's patented 'Green Spot' technology for good-read feedback (Green Spot only available on standard range imagers)
 - Auto Range Imager for near/far 2D scanning
 - Now with DPM support on standard range 2D models
 - DotCode support on the DL Focus 2D Imager models
- Choice of Microsoft Windows Embedded Compact 7 or Android v4.4
- TI 802.11 a/b/g/n radio with CCX v4 compliance and featuring MIMO antenna technology
- 1 GB RAM / 8 GB Flash memory
- Bluetooth® wireless technology v4.0 with BLE (low energy) and Wide Band Audio for improved speech recognition (Android models only)
- Corning® Gorilla® Glass 3 scan window
- WEC7 units include:
 - Wavelink® Avalanche™ and Terminal Emulation pre-installed and pre-licensed
 - Pal pre-installed and pre-licensed
- Upgradable to Android 4.4
- Attachable handle (and orderable pre-installed)
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY - APPLICATION

- Warehouse and Distribution Centers: Retail, Wholesale, Manufacturing, Automotive/ Industrial, Electronics, Food/Beverage, Consumer Products, Pharmaceutical, Third Party Logistics (3PL)
 - · Receiving
 - · Cross Docking
 - Put Away
 - Staging
 - Voice Picking
 - Shipping
 - · Cycle Count
 - Inventory
 - Shelf Replenishment
 - · Price Management
 - · Order Entry
 - Assisted Sales
 - Production Control







FALCON™ X4

TECHNICAL SPECIFICATIONS

WIRELESS COMMUI	VICATIONS	READING PERFORM	TANCE
Local Area Network (WLAN)	TI Wi-Link 8, IEEE 802.11a/b/g/n; Frequency Range: Country dependent, typically 2.4 and 5 GHz; Cisco CCX v4 compliant	2D Imager (Standard Range)	Megapixel sensor for extended range; White LED Illumination Optical Resolution: 1D codes: 3 mils; 2D codes: 6.6 mils Depth of Field (typical): 4.5 to 74 cm / 1.7 to 29.1 in (13 mil/EAN), depending on bar code density and type; DPM Support
Personal Area Network (WPAN)	Bluetooth wireless technology v4 with BLE (Android models) Bluetooth® v2.1 + EDR (WEC7 models)		
DECODING CAPABII	LITY		Megapixel sensor for extended range;
1D / Linear Codes	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.	2D Imager (DL Focus)	White LED Illumination Optical Resolution: 1D codes: 3 mils; 2D codes: 6.6 mils Depth of Field (typical): 4.5 to 42 cm / 1.7 to 16.5 in (13 mil/EAN), depending on bar code density and type DPM Support; DotCode Support
2D Codes	Aztec Code, Data Matrix, MaxiCode, PDF417, MicroPDF417, Micro QR Code, QR Code		
Postal Codes	Australian Post, Japanese Post, KIX Code, Royal Mail, USPS Intelligent Mail, USPS PLANET, USPS, Postnet		Optical Resolution: 1D codes: 3 mils; 2D codes: 10 mils Depth of Field (typical): 10 mil/Code 39: 0.16 to 3.1 m / 0.5 to 10 ft 55 mil/Code 39: up to 8.5 m / 28 ft 100 mil/Code 128: up to 17 m / 55 ft 10 mil/Code and the sum of 1.1 m / 1.4 to 3.6 ft 55 mil/Datamatrix: 0.4 to 1.1 m / 1.6 ft 100 mil/Datamatrix: up to 4.8 m / 16 ft 100 mil/Datamatrix: up to 8.3 m / 27 ft
Stacked Codes	GS1 Composite Codes UPC/EAN/JAN Composites, GS1 DataBar Composites and GS1-128 Composite		
ELECTRICAL		Auto Range 2D	
Battery	Removable battery pack with rechargeable Li-ion batteries; 3.7 V 5200 mAh (19.2 Watt hours)		
ENVIRONMENTAL			2500 pixel sensor; Sharp green LED scan line
Drop Resistance	Withstands drops from 1.8 m / 6.0 ft onto concrete follow IEC68-2-32 (Method 1) and 1500 random drops from 1.0 m / 3.3 ft follow EC68-2-32 (Method 2)	1D Imager	Optical Resolution: 2.5 mils (linear codes) Depth of Field: 4.0 to 74 cm / 1.5 to 29.1 in (13 mil/EAN), depending on bar code density and type
Particulate and Water Sealing	IP65	Scan Window	All scan engines feature Corning® Gorilla® Glass 3 scan window
Temperature	Operating: -20 to 50 °C /-4 to 122 °F Storage: -30 to 70 °C / -22 to 158 °F	SOFTWARE	
NTERFACES	otologe. Oo to 70 O7 EE to 100 T	Applications	Pal Application Library pre-licensed (WEC7 only)
Interfaces	Main connector with USB 2.0 High Speed Host (480 Mbps) and Client, RS-232 up to 115.2 Kbps; Ethernet or Modem: via single-slot dock (external module)	Configuration and Maintenance	Wavelink Avalanche® pre-licensed (WEC7 only), 42 Gears SureLock pre-licensed for device lockdown (Android only); SOTI MobiControl (optional), Datalogic xPlatform Utility (DXU) pre-licensed, Datalogic Desktop Utility (DDU) pre-licensed for device lockdown (WEC7 only)
PHYSICAL CHARAC	TERISTICS		
Audio	Integrated microphone, high-volume speaker Handheld: 22.5 x 8.8 x 5.5 cm / 8.9 x 3.5 x 2.2 in;		
Dimensions	6.4 x 4.0 cm / 2.5 x 1.6 in at keyboard Pistol grip: 22.5 x 8.8 x 16.8 cm / 8.9 x 3.5 x 6.6 in	Development	WEC7: Datalogic Windows SDK™ Android: Datalogic Android SDK, Xamarin SDK
Display	Reflective TFT daylight readable color display, 240 x 320 pixels, 8.9 cm / 3.5 in diagonal,	Browser	SureFox locked web browser pre-licensed for WEC7 and Android models
Keyboard	65K colors, backlight, touchscreen Polycarbonate hard cap keyboards with backlight; 29-key numeric, 29-key functional numeric or 52-key alphanumeric with discrete navigation	Terminal Emulation	Wavelink® Terminal Emulation™ pre-licensed (for WEC7 models only); StayLinked SmartTE (for Android); Wavelink Velocity (for Android)
Weight	Hand held: 602.0 g / 21.2 oz	SYSTEM	
	Pistol grip: 668.0 g / 23.6 oz	Audio	Wideband Speech (HD Audio) supported on Android
SAFETY & REGULAT	The product meets necessary safety and regulatory	Expansion Slots	Micro Secure Digital slot (SDHC) up to 32 GB, user-accessible
Agency Approvals	approvals for its intended use. The Users Manual for this product can be referred to for a complete list of certifications	Memory	RAM Memory: 1 GB Flash Memory: 8 GB (partially used for firmware and reserved data)
Environmental Compliance	Complies to EU RoHS	Microprocessor	TI OMAP4 @ 1 GHz
Laser Classification CFR 1040.1	VLD - Class 2 IEC/EN60825-1. Compliant with 21 CFR 1040.10 except for deviations pursuant to laser notice Number 50, dated June 24, 2007.	Operating System	Microsoft Windows Embedded Compact 7 (WEC7) or Android v4.4*
LED Classification	Exempt Risk Group IEC/EN62471	Real-time Clock	Time and date stamping under software control
State-greaters			roid 4.4 or from Android 4.4 to WEC7 is supported on all
\wedge		Falcon X4 configurations. The	OS swap must be performed at a Datalogic Service Cent
nde .			

Caution: Laser Radiation - do not stare into beam **ACCESSORIES**

2D Imager (Standard Range)	Megapixel sensor for extended range; White LED Illumination Optical Resolution: 1D codes: 3 mils; 2D codes: 6.6 mils Depth of Field (typical): 4.5 to 74 cm / 1.7 to 29.1 in (13 mil/EAN), depending on bar code density and type; DPM Support			
2D Imager (DL Focus)	Megapixel sensor for extended range; White LED Illumination Optical Resolution: 1D codes: 3 mils; 2D codes: 6.6 mils Depth of Field (typical): 4.5 to 42 cm / 1.7 to 16.5 in (13 mil/EAN), depending on bar code density and type; DPM Support; DotCode Support			
Auto Range 2D	Optical Resolution: 1D codes: 3 mils; 2D codes: 10 mils Depth of Field (typical): 10 mil/Code 39: 0.16 to 3.1 m / 0.5 to 10 ft 55 mil/Code 39: up to 8.5 m / 28 ft 100 mil/Code 128: up to 17 m / 55 ft 10 mil/Datamatrix: 0.4 to 1.1 m / 1.4 to 3.6 ft 55 mil/Datamatrix: up to 4.8 m / 16 ft 100 mil/Datamatrix: up to 8.3 m / 27 ft			
1D Imager	2500 pixel sensor; Sharp green LED scan line Optical Resolution: 2.5 mils (linear codes) Depth of Field: 4.0 to 74 cm / 1.5 to 29.1 in (13 mil/EAN), depending on bar code density and type			
Scan Window	All scan engines feature Corning® Gorilla® Glass 3 scan window			
SOFTWARE				
Applications	Pal Application Library pre-licensed (WEC7 only)			
Configuration and Maintenance	Wavelink Avalanche® pre-licensed (WEC7 only), 42 Gears SureLock pre-licensed for device lockdown (Android only); SOTI MobiControl (optional), Datalogic xPlatform Utility (DXU) pre-licensed, Datalogic Desktop Utility (DDU) pre-licensed for device lockdown (WEC7 only)			
Development	WEC7: Datalogic Windows SDK™ Android: Datalogic Android SDK, Xamarin SDK			
Browser	SureFox locked web browser pre-licensed for WEC7 and Android models			
Terminal Emulation	Wavelink® Terminal Emulation™ pre-licensed (for WEC7 models only); StayLinked SmartTE (for Android); Wavelink Velocity (for Android)			
SYSTEM				
Audio	Wideband Speech (HD Audio) supported on Android			
Expansion Slots	Micro Secure Digital slot (SDHC) up to 32 GB, user-accessible			
Memory	RAM Memory: 1 GB Flash Memory: 8 GB (partially used for firmware and reserved data)			
Microprocessor	TI OMAP4 @ 1 GHz			
Operating System	Microsoft Windows Embedded Compact 7 (WEC7) or Android v4.4*			
Real-time Clock	Time and date stamping under software control			



• 94A150057 Single Slot • 94A150056 Dock w/Spare Battery Charging Slot



Multi-Ethernet Dock Charges 4 terminals and 4 Batteries



Vehicle Dock

Battery Chargers



• 94A151137 Multi Battery Charger

Warranty



Multi Charge Only Dock Charges 4 terminals and 4 Batteries

Cases/Holsters

1-Year Factory Warranty



• 94ACC0104 Rubber Boot



• 94ACC0047 Standard Softcase with Quick Release Belt Clip

© 2019-2020 Datalogic S.p.A. and/or its affiliates. • All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic Sp.A. and/or its affiliates. Datalogic and the Datalogic logo are registered trademarks of Datalogic Sp.A. in many countries, including the U.S. and the E.U. • Falcon is a trademark of Datalogic S.p.A. and/or its affiliates. • SoftSpot is a trademark of Datalogic S.p.A. and/or its affiliates, registered in the E.U. • Android is a trademark of Google Inc. • The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic Group companies is under license. • All other trademarks and brands are property of their respective owners • Product specifications are subject to change without notice. • DS-FALCONX4-ENA4 Revision G 20200115