

MX-1000 SERIES MOBILE TERMINAL

The MX-1000 series mobile terminal allows you to leverage the latest mobile devices for your industrial barcode reading applications. The MX platform is both rugged and modular. The flexible design accepts a variety of both current and future generation smartphones and augments their capability in a fully ruggedized housing, tough enough to stand up to the most challenging environments. The MX-1000 and MX-1100 have patented class-leading 1DMax[®] and 2DMax[®] algorithms to give the fastest barcode reading performance on both 1D, 2D and even challenging direct part mark (DPM) codes. Put your mobile devices to work across your entire enterprise.

> RUGGED

The design of the MX-1000 series makes any supported mobile device ready to meet the challenges of the most demanding environments. The industrial-grade, rugged housing can handle up to 50 drops from 2 meters onto concrete. It is IP-65 sealed and uses inductive wireless charging so there are no exposed electrical contacts to wear out or fail.

> MODULAR

The MX platform is also future-proof and accepts a variety of Android[®] and iOS[®] smartphones. If your device needs to be repaired or upgraded, simply exchange the top cover kit to adapt the MX-1000 series to any supported mobile device. The modular design means your investment is protected and you are always ready for the latest technology. The pistol grip accessory doubles the MX-1000 series battery capacity that powers both the scan engine and the mobile device.



> SMART



MX-1000 and MX-1100 mobile terminals are equipped with world-class barcode reading algorithms. 1D and 2D label-based codes as well as challenging 2D DPM codes can be read quickly and easily. The MX-1000 series leverages the latest communication technologies supported by your mobile device including 3G, 4G, 4G LTE, Wi-Fi, Bluetooth and more.



Proven performance

The MX-1000 and MX-1100 are ideal for applications in any industrial environment that requires robust 1D and 2D barcode reading technology.

- Couriers
- Field service
- Parcel delivery
- Transportation
- Logistics
- Utilities
- Telecommunications
- Cable companies
- Pharmaceutical
- Tobacco
- Automotive
- Manufacturing



Accessories

The MX-1000 series has a selection of available accessories for charging and handling.



The sturdy belt holster attaches comfortably and easily to any size belt and is made of industrial-grade materials to withstand heavy daily use.

The pistol grip handle offers an alternative configuration for comfortable “point & shoot” barcode reading. The handle contains a secondary battery that doubles the power capacity.



The wireless charging station eliminates charge failures from poor connections ensuring a full

charge in less than 6 hours. The spare battery can be fully charged in less than 4 hours.



WALZ

Label & Mailing Systems
624 High Point Ln., East Peoria, IL 61611-9329
(309) 698-1500 T/F (877) 971-1500
www.walzeq.com email: walz@walzeq.com

MX-1000 SERIES SPECIFICATIONS

Dimensions	208.6 mm x 88.9 mm x 42.1 mm
Weight	510 g (675 g with pistol grip)
Operating Temperature	0 °C to 40 °C (32 °F to 104 °F) *
Storage Temperature	-40 °C to 60 °C (-40 °F to 140 °F) *
Maximum Humidity	95% (non-condensing)
Material	Polycarbonate housing with overmold
Imager	752 x 480 global shutter sensor
Aiming	Green LED
Status Outputs	LED, beeper and vibration
Communications	Scan engine communicates to mobile device through USB port. Mobile device communicates via Wi-Fi, Bluetooth, Cellular and others based on model.
Supported Devices	Samsung® Galaxy® S6, S7, S8, S9, S10e, and J3 (J320, J327, J330, J337), Nokia 4.2, Apple® iPhone® 5/5S, SE, 6/6S, 7, 8, X, XS, 11 Pro, and iPod® 6th and 7th Generations
Symbologies	1D: UPC/EAN/JAN, Codabar, Interleaved 2 of 5, Code 39, Code 128, Code 93, Pharmacode, GS1 DataBar, PDF417, Micro PDF417 2D: Data Matrix, QR Code, MicroQR Code, DotCode, and postal code
Lighting	Integrated LED illumination
Base Station Power Supply Requirements	24 V, 13 W maximum LPS or NEC Class 2 power supply
Battery (brick style)	3.7 V, 3070 mAh Li-Polymer
Battery (pistol grip)	3.7 V, 3100 mAh Li-Ion
Environmental	Compliant with RoHS directive 2002/98/EEC
Regulatory Electrical EMI/RFI	CB Scheme: IEC 60950-1, UL 60950-1, CSA C2.2 No. 60950-1-07 FCC 47 CFR Part 15 Subpart B, CE, ICES-003, KCC
Data Validation	US DoD UID Guidelines, GS-1, ISO15434 and ISO15418
Trigger	Left- and right-handed buttons, pistol grip or touch screen software
IP Rating	IP65

* Value for MX-1000. Max temperature varies by mobile device.

MX-1000 SERIES SCAN CHART

	MX-1000	MX-1100
5mil 1D Code	Up to 125 mm	Up to 165 mm
10mil 1D Code	Up to 200 mm	Up to 280 mm
20mil 1D Code	Up to 280 mm	Up to 510 mm
10mil 2D Code	Up to 125 mm	Up to 152 mm
20mil 2D Code	Up to 200 mm	Up to 355 mm

COGNEX

Companies around the world rely on Cognex vision and barcode reading solutions to optimize quality, drive down costs and control traceability.

Corporate Headquarters One Vision Drive Natick, MA 01760 USA | For Regional Sales Offices, visit www.cognex.com/sales

www.cognex.com

© Copyright 2020, Cognex Corporation. All information in this document is subject to change without notice. All Rights Reserved. Cognex, the Cognex logo, Cognex.com 1DMax and 2DMax are registered trademarks of Cognex Corporation. All other trademarks are the property of their respective owners. Lit. No. MX1000-DS-04-2020-EN