THOR VM1A

Vehicle-Mounted Computer

Forklifts and vehicle-mounted computers are essential tools in the day-to-day workflows of warehouses, manufacturing, ports and intermodal environments.

You need to keep moving products and materials in and out all day long, without compromise, and without worrying that your vehicle-mounted computer won't be able to keep up with your workforce or your IT infrastructure. You need the Thor™ VM1A.

Built with many of the same easy-to-use, easy-to-maintain features as the popular Thor VM1 and CV41 models, the rugged, Android[™]-based Thor VM1A also offers all the advantages of Honeywell's Mobility Edge[™] platform – including the ability to accelerate provisioning, application certification and deployment across the enterprise. The Thor VM1A is upgradable from Android O to Android R, and features extended security update support to maximize return on customer investment and provide a lower overall TCO. The device's advanced enterprise configuration and software support tools also simplify frequently repeated tasks such as unit setup and distribution of security and software updates.

Compact, ergonomic and powerful, the Thor VM1A has numerous breakthrough features designed to maximize productivity, minimize visual obstructions and reduce or eliminate downtime. The powerful Qualcomm® 660 processor, integrated keyboard and 2x2 MIMO WLAN communications keep workers connected and productive. Built to withstand extreme temperatures, the device's large 8-inch display, readable both indoors and outdoors, supports both resistive and capacitive touchscreen options, and is available with an optional screen defroster for use in cold storage and freezer environments.

The Smart Dock feature delivers immediate savings on support and maintenance costs while maximizing efficiency, enabling users to quickly shift computers as vehicles fail or workloads change. The field-replaceable front panel allows enterprises to minimize investments in spare parts by substituting low-cost spare front panels for spare computers, and saves valuable time and maintenance costs by leveraging in-house staff to service touchscreen or keyboard failures.



Built on the future-proof Mobility Edge platform, the Android-based Thor VM1A vehicle-mounted computer is built tough to handle harsh warehouses, ports and intermodal and manufacturing environments.

FEATURES AND BENEFITS



The Smart Dock feature enables mounting and removal in seconds without affecting the cabling, saving on support and maintenance costs while minimizing capital expenses.



The field-replaceable front panel reduces maintenance costs by enabling on-site unskilled personnel to service the most wear- and abuse-prone components rather than returning them to the repair depot.



Security update availability is just as important as computer durability for maximizing a computer's useful life. Mobility Edge products provide five more years of security updates than a typical Android device.



No need to choose between optimizing productivity and minimizing IT support costs: All Honeywell Mobility Edge computers share a common hardware and software platform. From an IT perspective, they are all the same product.



The Mobility Edge hardware platform and enterprise lifecycle tools drive an integrated, repeatable, scalable approach for accelerated and secure development, deployment, performance and lifecycle management.



THOR VM1A Technical Specifications

SYSTEM ARCHITECTURE

Processor: 2.2 GHz Qualcomm Snapdragon™ 660 octa-core Operating System: Android 8 (Oreo), upgradable through Android R

Memory: 4 GB RAM, 32 GB Flash Storage Expansion: User-accessible microSD card up to 512 GB (SDXC/SDHCcompliant)

Audio: Audio for headset, integrated stereo speakers with adjustable volume control, integrated microphone

Input/Output:

Enhanced Dock: 2x powered RS-232 COM ports, 1x USB 2.0 powered host port Type A, 3 additional USB 2.0 powered host ports, 1x USB 2.0 Client port, 1x Ethernet RJ45 port, 1x CANbus port, 1x headset port, DC power input and ignition control input

Standard Dock: 2x powered RS-232 COM ports, 1x USB 2.0 powered host port, 1x USB 2.0 Client port, 1x CANbus port, 1x headset port, DC power input and ignition control input

Computer: 2x SMA connectors for external WLAN antennas

Sensors: Ambient light sensor, accelerometer, gyroscope, magnetometer Display: 20 cm (8 in) WXGA (1280 x 768) LED backlit display, standard 400 NIT indoor display, optional 900 NIT outdoor display, optional screen blanking

Touch Panel:

Resistive: Industrial touch panel with support for finger touch and standard stylus; supports swipe

Capacitive: PCAP multi-touch touch panel for finger and conductive stylus; hardened glass overlay. Automatic detection and configuration utilizing mutual and self-capacitance modes for water rejection and use with many offthe-shelf gloves

Cold Storage: Optional industrial resistive touchscreen with integrated defroster **Keypad:** Full 64-key QWERTY keyboard with number pad and 10/20 function keys; all keys, except modifiers, are mappable; all keys backlit; key labels support ANSI and 5250 emulation

Power Supply and UPS: 10 to 60V DC isolated, optional external converters for AC (90 to 240V AC) and extended range DC (60 to 150V DC); integrated Li-Ion maintenance UPS with 30-min life at 20°C (68°F), charging range 0°C to +35°C (32°F to +95°F)

ACCESSORIES

Compatible with the VM series of accessories

MECHANICAL

Dimensions (L x W x H): Computer: 268 mm x 214 mm x 43 mm(10.6 in x 8.4 in x 1.7 in) Weight: 2.1 kg (5.6 lb)Dock: 180 mm x 155 mm x 64 mm(7.1 in x 6.1 in x 2.5 in) Weight: 1.2 kg (3.2 lb)

ENVIRONMENTAL

Operating Temperature: -30°C to 50°C (-22°F to 122°F)

Storage Temperature: -30°C to 70°C (-22°F to 158°F)

Humidity: 5% to 95% relative humidity (non-condensing)

Vibration: MIL-STD-810F, composite wheeled vehicles

Shock: SAE-J1455

ESD: EN55024:1998 (enhanced ESD to 8 kV direct and 15 kV air)

Environmental Sealing: Independently certified to meet IP66 standard for moisture and particle intrusion

WIRELESS CONNECTIVITY

WLAN: IEEE 802.11 a/b/g/n/ac; Wi-Fi Alliance Certified, 2x2 MU-MIMO

Additional WLAN Features: 802.11 d/h/i/r/k/w

WLAN Security: OPEN, WEP, WPA/WPA2 (Personal and Enterprise)

Supported EAP: TLS, PEAP, TTLS, PWD, FAST, LEAP CCX Version 4 compliant WLAN Antennas: Dual internal antennas,

dual external remote and direct connect antenna accessories

Bluetooth®: Class 1.5 V5.0 Bluetooth and BLE

Bluetooth Profiles: HFP, PBAP, A2DP, AVRCP, OPP, SPP, GATT NFC: Integrated Near Field Communication

SOFTWARE

Honeywell Power Tools and Demos Terminal Emulator Enterprise Browser Application Launcher and Lockdown Provisioning Tools Honeywell Mobility SDKs for Android, Web and Xamarin Support for Third-Party MDM Solutions

WARRANTY

One-year factory warranty

SERVICE PLANS

Optional service programs offer worryfree mobile computing

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/ compliance.

For a complete listing of all supported barcode symbologies, please visit www.honeywellaidc.com/symbologies.

Thor and Mobility Edge are trademarks or registered trademarks of Honeywell International Inc.

Android is a trademark or registered trademark of Google LLC.

Qualcomm and Snapdragon are trademarks or registered trademarks of Qualcomm Incorporated.

Bluetooth is a trademark or registered trademark of Bluetooth SG, Inc.

All other trademarks are the property of their respective owners.

For more information

www.honeywellaidc.com

Honeywell Safety and Productivity Solutions

9680 Old Bailes Road Fort Mill, SC 29707 800-582-4263 www.honeywell.com





THE FUTURE IS WHAT WE MAKE IT

Thor VM1A Data Sheet | Rev C | 03/20 © 2020 Honeywell International Inc.

